



ARLANXEO

Performance Elastomers

**PERFORMANCE POLYMERS
FOR ADHESIVES AND SEALANTS
PRODUCT PORTFOLIO**

www.arlanxeo.com

PORTFOLIO

Baypren®

Fast crystallizing grades

Grade	Chip-thickness [mm]	Viscosity [mPa·s] 10 wt% solution in toluene
Standard grades		
Baypren® 310-1	approx. 2	70 – 220
Baypren® 320-1	approx. 2	350 – 550
Baypren® 320-2	approx. 2	550 – 810
Baypren® 330-1	approx. 2	700 – 1,000
Baypren® 330-2	approx. 2	900 – 1,400
Baypren® 340-2	approx. 1	1,600 – 2,500
Baypren® 350-1	approx. 1	2,200 – 4,000
Baypren® 350-2	approx. 1	2,500 – 5,300
Thiuram modified grade		
Baypren® 321-1	approx. 2	350 – 550

Medium fast crystallizing grades

Grade	Chip-thickness [mm]	Viscosity [mPa·s] 10 wt% solution in toluene
Standard grades		
Baypren® 213-1	up to 10	70 – 220
Baypren® 213-2	approx. 2	220 – 380
Baypren® 223-2	approx. 2	550 – 810
Baypren® 233-1	approx. 2	700 – 1,000
Baypren® 233-2	approx. 2	900 – 1,400
Baypren® 243-2	approx. 2	1,600 – 2,500
Baypren® 253-1	approx. 2	2,200 – 4,000
Baypren® 253-2	approx. 2	2,500 – 5,300
Pre-crosslinked grade		
Baypren® 214	up to 10	50±6 MU ⁽¹⁾

⁽¹⁾ ML (1+4) 100°C unmassed (ISO 289-1) MU (Mooney units)

Supply form

Baypren® is supplied in form of chips with about 2 cm length, 1 cm width and a thickness of 1-10 mm.

The chips are talcum coated and packed in 25 kg bags.



■ Thickness of chips up to 10 mm:
Baypren® 213-1 and Baypren® 214



■ Thickness of chips approx. 2 mm:
Baypren® 213-2 to 253-2
and 310-1 to 330-2



■ Thickness of chips approx. 1 mm:
Baypren® 340-2 to 350-2

Your contact to Baypren® experts: baypren@arlanxeo.com; webpage: baypren.com