

Lion Copolymer Geismar, LLC

36191 Highway 30 • Geismar , LA 70734 800 / 535-9960 • www.lionelastomers.com

Royalene® 511 EPDM

Product Data

" An Excellent Low Viscosity Polymer for High Quality Mechanical Goods "

Unique Features

- Low Mooney viscosity
- Excellent processing characteristics
- ▶ Blends easily in all formulations
- Outstanding low temperature properties
- Excellent weathering

Applications

- ▶ Automotive parts such as brake system components
- Mechanical goods
- Press molded sponge

Raw Polymer Properties

	Test Method*	Typical
Mooney Viscosity, ML (1+4)/100°C (Unmilled)	ZS 1220B	45
E/P Weight Ratio	ZS 1231 monlore	57/43
ENB, Weight %	ZS 1222	4.6
Molecular Weight Distribution	ZS 1296A	Medium
Volatile Matter, Weight %	ZS 1008K	1.0 Max.
Stabilizer	_	Non-Staining
Specific Gravity, g/cc	ASTM D-792	0.86
Color	ZS 1072A	Off White
Physical Form, lbs/bale	- (5)	55.1 (25 kg)
		(Dense bale)

^{*} Company Test Methods

Royalene® 511 has FDA Compliance with several FDA titles, including 21CFR: §177.2600, rubber articles intended for repeated use. Consult the FDA title for use and restrictions. See also the Royalene FDA Summary for other FDA titles.

Royalene 511