



ETHYLENE PROPYLENE DIENE RUBBER

DESCRIPTION

SABIC EPDM 756 is a high mooney viscosity, high ethylene and medium ENB content grade produced by solution polymerization using metallocene catalyst. It has medium molecular weight distribution. This product is available in pellet form

TYPICAL APPLICATIONS

SABIC EPDM 756 can be used for: industrial hoses, automotive hoses and belts, extruded profiles, auto weather seals, heat resistant applications

TYPICAL PROPERTY VALUES

Revision 20201023

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
POLYMER PROPERTIES			
Mooney viscosity (ML 1+4, 125 °C) (1)	72	MU	ASTM D1646
Ethylene Content	69	Wt.%	ASTM D3900
Ethylidene Norbornene (ENB) Content	5	Wt.%	ASTM D6047

(1) Polymer remassed at 140 ± 5° C

CHARACTERISTICS

SABIC EPDM 756 is designed for: smooth and fast extrusion, improved mixing, mill handling and physical properties, excellent oil retention and improved cure bloom in compounds, high filler loadable

STORAGE AND HANDLING

SABIC EPDM 756 should be stored in its original packing at ambient temperature in dry conditions; flowability of the pellets can be negatively influenced by pressure or high temperature; exposure to heat, ultraviolet light and direct sun light should be avoided. Under suitable storage conditions, the product is stable for 24 months from the date of manufacture. SABIC will not extend its warranty when storage conditions are inadequate which may lead to quality deterioration such as pellet hardening or color change that could result in inadequate product performance.

DISCLAIMER

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.