

TECHNICAL DATA SHEET

BUDENE® 1224

CHEMICAL DESCRIPTION

BUDENE[®] 1224 is a solution polymerized high cis-1,4 polybutadiene stabilized with a non-staining antioxidant.

This polymer is produced using a stereospecific Neodymium catalyst which controls molecular weight distribution and provides a highly linear polymer.

APPLICATIONS

BUDENE[®] 1224 is typically blended with other elastomers to help achieve benefits in applications requiring enhanced:

- Abrasion resistance
- Flex-cracking resistance
- Resilience
- Low temperature properties

Application areas may include:

- Tire compounds
- Automotive and conveyor belts
- Hoses and tubes
- Shoe products
- Mechanical goods
- Sporting goods

TYPICAL PROPERTIES

Color	BUDENE [®] 1224 light amber
Mooney ML1+4 @ 100°C	44
Onset Tg, °C	-110
Cis 1,4, Content, %	97
Volatiles, %	0.5 max
Specific Gravity	0.91
Stabilizer	non staining

PACKAGING

Returnable Containers

- Returnable containers are collapsible aluminum containers that contain 36 80 lb film wrapped bales.
- Contact your sales representative for details. Other packaging types may be available for specific volumes and destinations

STORAGE AND HANDLING

- BUDENE[®] 1224 may be stored in its original packaging in a dry atmosphere away from heat and ultraviolet light.
- BUDENE[®] 1224 release properties can be re-tested every 24 months.

Goodyear International Corporation

2000 Goodyear Dr, Houston, TX 77017 1-800-548-8107 WARRANTY: Unless sold without warranty, this product is warranted to conform to Goodyear's applicable specifications in effect at the date of shipment. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. NO OTHER WARRANTY OF ANY KIND WHATSOEVER, EITHER ORAL OR WRITTEN, INCLUDING IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHER WARRANTY OF QUALITY IS EITHER EXPRESSED OR IMPLIED FOR THIS PRODUCT. GOODYEAR SHALL NOT BE LIABLE FOR SPECIAL, INCIDENTAL AND/OR CONSEQUENTIAL DAMAGES, EVEN IF GOODYEAR HAS BEEN NOTIFIED OF THE POTENTIAL OF SUCH A LOSS OR CLAIM OR FOR ANY AMOUNT IN EXCESS OF THE APPLICABLE PURCHASE PRICE. This warranty is null and void should the product be subject to abuse, modification, misused or mishandled. (@Trademark, The Goodyear Tire & Rubber Company